



**DEXRON III/ MERCON
Multi-Purpose Automatic Transmission Fluid**

Description:

- Imperial *MP ATF* is a high performance multipurpose power transmission fluid that is specially formulated for systems requiring DEXRON[®]-III and MERCON[®] finished oils.
- IPAC *MP ATF* is manufactured using highly re-refined paraffinic base oils and a select additive package with an extremely shear stable V.I. improver.
- IPAC *MP ATF* provides superior thermal and oxidative stability, corrosion and wear protection, that will prevent the formation and accumulation of deposits and sludge.

Typical Applications:

- IPAC *MP ATF* is acceptable for use in passenger cars and light-duty trucks where the manufacturer recommends a DEXRON[®] or MERCON[®] fluid.

Physical Properties:

API Gravity	33.1
Color, ASTM D-1500	2.5 max
Viscosity, @ 40°C, cSt	34.15
Viscosity, @ 100°C, cSt	7.4
Viscosity Index	191
Flash Point (PMCC), °C	>170
Pour Point, °C	-41
Appearance	Red

Storage & Handling:

Maximum temperatures of 60°C (140°F) for handling and 38°C (100°F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed. The test results listed are typical properties only.

“Success is in the Details”